



# Room Display

## DS7315

Room Display DS7315 is a digital signage collaborating with Yeastar Meeting Room Booking System to **display meeting room availability in real-time** using traffic light LED indicators. Mounted at the entrance of each meeting room, it enables employees to easily locate available rooms by identifying the colors from a distance.

Equipped with a **15.6-inch touch screen**, Room Display DS7315 meets the demand for larger screens. Tap to reserve, check in, extend, and end meetings **on the spot**. In case of an impromptu team huddle, just tap to start the meeting, and the room status will change accordingly with LED lights switching from green to red.

**Identity authentication and access control integration** combined will empower you to manage meeting room utilization with higher granularity. As people reserve, check in, or end meetings on the Room Display, they will be asked to verify their identities on the spot via facial recognition or QR code scans.

- Collaborates with Yeastar Meeting Room Booking System to display the latest meeting schedules, start an ad-hoc meeting, check-in & check-out, extend meetings
- Add your company's logo, set up background pictures, and customize any 3 LED light colors to signal meeting room status
- Works with Yeastar People Counting Sensor to update in-room attendees in real-time
- Managed and monitored remotely by the cloud-based Yeastar Workplace platform
- Built-in camera supports facial recognition on the spot
- Authenticate user identity via facial recognition or QR code scans
- Support integration with your existing access control system to restrict access to only authorized staff
- Support energy saving settings
- Hide/show meeting topic/organizer flexibly
- Plug-and-play PoE or DC power
- Provides easy installation and flexible mounting options

<b>Model</b>	
Room Display	DS7315
<b>Display</b>	
Touch Screen	15.6-inch LCD touch screen
Resolution	1920 x 1080 pixels
Active Area	344.3 (L) x 193.2 (H) mm
Aspect Ratio	16:9
<b>LED</b>	
LED	Four-Edge LED Indicators (16 colors available)
<b>Camera</b>	
Built-in Camera	500W pixels
<b>Connectivity</b>	
Wi-Fi	IEEE 802.11 b/g/n, 2.4GHz IEEE 802.11a/n/ac, 5 GHz
Wired connectivity	One 100M/1000M Ethernet port
Bluetooth	Bluetooth 4.2
System	Android 10.0
Power	Power over Ethernet (PoE) DC 12V/2A
<b>Interface</b>	
Serial Port	DI/DO
USB	USB 2.0
<b>Dimension &amp; Weight</b>	
Dimension	397.4 (L) x 256.4 (H) x 28.5 (D) mm
Weight	3 kg
Installation	Wall/Glass mount
<b>Environmental Conditions</b>	
Operating Temperature	0°C to +40°C
Operating Environment	In door use only